Carter floorline bed

Code (s) : 3550, 3555

The Carter floorline bed is a fully electric care bed designed to improve safety, comfort and independence. Its low floorline height helps reduce the risk of injury from falls, while the electric backrest, knee break and hi-low adjustment allow residents to find comfortable, supported positions throughout the day. Preset sleep and exit positions support easier transfers, and the warm timber finish gives the bed a homely appearance while maintaining full clinical functionality.



FEATURES

- Floorline design with ultra-low height to help reduce fall injury risk
- Electric hi-low height adjustment with simple handset control
- Backrest elevation and knee break for comfortable positioning
- Auto-regression backrest helps minimise pressure and shear
- Preset sleep and exit positions support safer transfers
- Backlit handset allows easy control in low light environments
- Integrated bed extension up to 200mm for taller residents
- Removable head and footboards allow clinical access when required
- Mattress retainers keep the mattress securely positioned
- Central locking castors for stability and easy repositioning

Carter floorline bed

SPECIFICATIONS

Code(s)	3550	3555
Option	Single	King single
Overall dimensions	W 960 L 2180 – 2380mm	W 1110 L 2180 – 2380mm
Sleeping surface dimensions	W 900 L 2000mm	W 1050 L 2000mm
Safe working load	250kg	250kg
Electric specification	Four-section electric bed including backrest elevation and knee break	Four-section electric bed including backrest elevation and knee break
Function	Trendelenburg / Reverse Trendelenburg	Trendelenburg / Reverse Trendelenburg
Comfort positions	Automatic comfort seating and mattress compensation	Automatic comfort seating and mattress compensation
Bed extension	Integrated bed extension up to 200mm	Integrated bed extension up to 200mm
Colour	Linberg oak	Linberg oak
Braking system	Central braking system	Central braking system
Height adjustment range	110 - 735mm	110 - 735mm
Backrest angle adjustment	0 - 70°	0 - 70°
Knee break angle adjustment	0 - 36°	0 - 36°
Trendelenburg adjustment	0 - 12°	0 - 12°
Trendelenburg / Reverse Trendelenburg	Both	Both
Protection class	IPX4	IPX4